

M923 Signal Straight Male Socket (Crimp, Mount hole 19.8x19.8)

尺寸图

接线定义

芯位 Pins	线芯颜色 Wire core color		导体规格 Conductor size
	6芯(Pins)		
1	BK	U	1.5mm ²
2	BN	V	1.5mm ²
3	GN	YE	1.5mm ²
4	BK		1.5mm ²
5	WH		1.5mm ²
6	BN	K	1.5mm ²

芯位 Pins	线芯颜色 Wire core color		导体规格 Conductor size
	8芯(Pins)		
1	BK	1	1.5mm ²
PE	GN	YE	1.5mm ²
3	BK	2	1.5mm ²
4	BK	3	1.5mm ²
A	BK	5	0.75mm ²
B	BK	6	0.75mm ²
C	BK	7	0.75mm ²
D	BK	8	0.75mm ²

芯位 Pins	线芯颜色 Wire core color		导体规格 Conductor size
	12芯(Pins)		
1	PK		0.25mm ²
2	RD		0.25mm ²
3	BK		0.25mm ²
4	BU		0.25mm ²
5	BN		0.25mm ²
6	GN		0.25mm ²
7	VT		0.25mm ²
8	GY		0.25mm ²
9	外部护套		(Outer sheath)
10	WH		0.5mm ²
11	NC		
12	BN		0.5mm ²

芯位 Pins	线芯颜色 Wire core color		导体规格 Conductor size
	17芯(Pins)		
1	YE		0.14mm ²
2	GN		0.14mm ²
3	RD		0.14mm ²
4	NC		
5	BU		0.14mm ²
6	NC		
7	BNBU		0.5mm ²
8	GNBK		0.22mm ²
9	GNRD		0.22mm ²
10	BNRD		0.5mm ²
11	BK		0.14mm ²
12	BN		0.14mm ²
13	OG		0.14mm ²
14	WHBK		0.14mm ²
15	BNGY		0.22mm ²
16	BNYE		0.22mm ²
17	内部护套		(Inner sheath)

*接线定义按常规标准，如按协议或者其他请联系我司业务。
Wiring definition according to conventional standards, if according to the agreement or other please contact our sales.

电气参数

芯数 Pins	针型 Male	额定电流 Rated current	额定电压 Rated voltage		导体规格 Conductor size		孔型 Female
			A/C	D/C	AWG	mm ²	
6		30A	630V	630V	14	2.5	
8		9A/20A	250V/630V	250V/630V	18/14	1/2.5	