F系列-ME1 固定式插座







■ 定位销(1,2,3), 电缆线夹

技术参数

221 2 201	
锁紧方式:	推拉自锁式
工作温度:	-45°C ~ +125°C
最大潮湿:	在60 ℃/140 °F 时最高达到95%
屏蔽性能:	>95dB(10MHz); >80dB(1GHz)
抗振动性能:	15g[10~20000Hz]
盐雾测试:	> 96h
抗冲击性能:	100g,6ms
机械寿命:	> 5000次
防护等级:	IP68







编号(Model)		尺寸(Size)								开孔尺寸(hole opening size)		
型号(Type)	系列(Series)	Α	В	L	Р	М	е	Е	S 1	S2	W	D
ME1	OF	12.0	14.0	19.2	6.5	3.0	M9*0.5	3.0	8.2	11.0	8.3	9.1
ME1	1F	18.0	18.0	24.8	8.0	3.5	M14*1	4.0	12.5	15.0	12.6	14.1
ME1	AF	18.0	18.0	23.1	7.0	3.5	M14*1	3.0	12.0	15.0	12.1	14.1
ME1	2F	20.8	20.8	24.2	8.0	3.5	M16*1	4.0	14.3	16.0	14.4	16.1

订购产品



