

| 芯数排列及技术参数 PINS ARRANGEMENT & TECHNICAL PARAMETERS | | | | | | | | | | | | | | | | |
|--|----------------------------|------|------|------------------------------|------|------|---------------------|------|------------------------------|-----|-----|-----|-----|-----|---------|-----|
| 芯数 Pins | 2B | 3B | 4B | 2 | 3 | 4 | 5 | 6 | 8C | 7 | 8 | 9 | 10 | 12 | 14 | 18 |
| 芯位排布 Pins arrangement | | | | | | | | | | | | | | | | |
| 芯数 Pins | 8C | 7 | 8 | 9 | 10 | 12 | 14 | 18 | | | | | | | | |
| 芯位排布 Pins arrangement | | | | | | | | | | | | | | | | |
| 规格 SPECIFICATIONS | | | | | | | | | | | | | | | | |
| 芯数 Pins | 2B | 3B | 4B | 2 | 3 | 4 | 5 | 6 | 8C | 7 | 8 | 9 | 10 | 12 | 14 | 18 |
| 线规 Wire gauge | 2.5mm ² (14AWG) | | | 0.823mm ² (18AWG) | | | 16AWG+ 22AWG | | 0.519mm ² (20AWG) | | | | | | 22AWG | |
| 引脚类型 Pin type | ∅ 2.4mm | | | ∅ 1.6mm | | | ∅ 2.0mm+ ∅ 0.8mm | | ∅ 1.0mm | | | | | | ∅ 0.8mm | |
| 接线范围 Wiring range | 6.0mm~10.0mm | | | | | | | | | | | | | | | |
| 防水等级 Waterproof grade | IP67/IP68 | | | | | | | | | | | | | | | |
| 插拔次数 Durability | 500 | | | | | | | | | | | | | | | |
| 适应温度 Applicable temperature | -45°C~105°C | | | | | | | | | | | | | | | |
| 额定电压 Rated voltage | 300V | 300V | 300V | 125V | 125V | 125V | 125V | 125V | 125+30V | 60V | 60V | 60V | 60V | 60V | 60V | 30V |
| 额定电流 Rated current | 20A | 20A | 20A | 20A | 20A | 10A | 10A | 10A | 15+2A | 5A | 5A | 5A | 5A | 5A | 5A | 2A |