


电气参数

芯数 Number of contact	2	3	4	5	6	7	8
公端绝缘体正面图 Male contact face view							
额定电流(A) Rated current	5	5	5	5	5	3	3
工作电压(AC.V) Rated voltage	125	125	125	125	125	100	100
耐压(AC.V) 1 min Test voltage	1500	1500	1500	1500	1500	1000	1000
接触电阻(mΩ) Contact resistance	5	5	5	5	5	5	5
接触件直径(mm) Contact diameter	φ 1.0x2	φ 1.0x3	φ 1.0x4	φ 1.0x5	φ 1.0x6	φ 0.8x7	φ 0.8x8
导体规格(mm²/AWG) Wire size	0.5/20	0.5/20	0.5/20	0.5/20	0.5/20	0.34/22	0.34/22
适用线径(mm) Cable O.D range	φ 4 ~ φ 5.5	φ 4 ~ φ 5.5	φ 4 ~ φ 5.5	φ 4 ~ φ 5.5	φ 4 ~ φ 5.5	φ 4 ~ φ 5.5	φ 4 ~ φ 5.5
机械寿命 Mechanical life	≥500 次(times)						
接线方式 Assembly style	焊接(Soldering)						
防护等级 Protection level	标配 IP65 / 可选 IP67 & IP68 (Standard is IP65, IP67 & IP68 Option Avaliable)						
工作温度 Temperature rating	-40℃ ~ +85℃						
外壳/绝缘部分 Shell & insulated parts	PBT						
金属部分 Hardware metal	锌合金(Zinc Alloy)						
接触铜针 Contact size	铜合金(Brass with gold-plated)						
防水材料 Sealing	硅胶/橡胶(Silicone/rubber)						
绝缘电阻(mΩ) Insulation resistance	≥500						
温升 Temperature rise	5A时温升在30K以下 (5A Per contact at 30K)						